

Visual Characteristics

EA6 Rental Frame

Product Code	T6.6
Use	Outdoor
Description	Brick LED module 6,67mm SMD
Virtual Res.	N
Cooling	fanless
LED type	SMD 3 in 1 (3528)
Pixel Pitch (mm)	6,67
Brightness (Nits)	5500
Viewing Angle (H) 50% Brightness	140 (+70/-70)
Viewing Angle (V) 50% Brightness	110 (+55/-55)
Contrast Ratio (Typical)	1000:1
Minimum Viewing Distance (m)	6,67
LED's per Pixel	SMD 3-in-1
Pixels per Square Metre	22478
LED's per Square Metre	22478
Colours (Panel)	281 trillion
Processing Depth (bit)	16
Video Frame Rate (Hz)	50/60
Display Refresh Rate (Hz)	2400
Operating Temperature (C)	-20 to 50
Lifetime (50% Brightness)	≥100,000
Warranty	24 Months
Frame Width(mm)	640
Frame Height (mm)	640
Frame Depth (mm)	95
Frame Diagonal (mm)	905
Frame Surface Area (m²)	0,41
Pixel Matrix H	96
Pixel Matrix V	96
Ingress Protection (Front/Rear)	IP65 / IP65
Max Power Consumption (W)	512
Weight (kgs)	22,8

